



Certificate of Testing

Customer: Anzea
Contact:

Report Number: 20662-2-24-21
Date: 2/24/2021

Pattern Number and Name: 20662 Beach Blanket

Content: 100% Poly

Finish: Crypton X135

Test Performed California Technical Bulletin 117: June 2013 – Requirements, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture—Cover Fabric Test

Test Results

Specimen	Char Length	Extinguished in 45 minutes (Y/N)
1	.5"	Y
2	.5"	Y
3	.5"	Y

Notes

Test Conditions: 70±5°F, 50±5% Relative Humidity

Acceptance Criteria

A material is considered to pass or fail based on the following criteria:

- 1) A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs.
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration
 - b) A vertical char length of more than 1.8 inches (45mm) develops on the cover fabric
 - c) The mock-up test specimen transitions to open flaming
- 2) The cover fabric passes the test if three initial mock-up specimens pass the test, i.e. the cigarettes burn their full length and are no longer smoldering
- 3) If more than one initial specimen fails, the cover fabric fails the test
- 4) If any one of the three initial specimens fails, repeat the test on additional three specimens
- 5) If all three additional specimens pass the test, the cover fabric passes the test. If any one of the additional three specimens fails, the cover fabric fails the test

Conclusion Based on the above Results and Acceptance Criteria, the item tested is:

Pass

Fail

Certification: I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Bobby Milam Finishing/ Inspection Manager
P: 828-202-5869
E: bobby.milam@abercrombietextiles.com