

ANZEA.

Fabric Testing Laboratory

Pattern Tested: 29903A1/29650A1 with Crypton

Date: 3/14/2014

Tested For: Anzea Textile's JAZZ

Test Performed: NFPA 260/UFAC Fabric Classification Test Method 1990
Cal 117-2013 based on prior testing to UFAC/NFPA 260
Cigarette Ignition Resistance of Fabric Intended for Use in Upholstered Furniture

RESULTS:

Specimen	Ignition (Yes/No/SE)	Char Length On Vertical Panel (inches)
#1	DNI	0.75
#2	DNI	0.63
#3	DNI	0.75

SE - Indicates that the cigarette self extinguished prior to burning its entire length. When this occurs, a "retest" of that specimen is performed

Remarks: NONE

Classification System:

- Class 1 - For each specimen: No obvious ignition; char length less than 1.75"
(Indicates propensity to resist cigarette ignition in conjunction with standard foam filling material.)
- Class 2 - For any specimen: Obvious ignition or char length 1.75" or greater
(Indicates inability to resist cigarette ignition with standard foam filling materials)

Conclusion: Based on the above results and acceptance criteria, the item tested is assigned a:

{ XX } Class 1 Rating
{ } Class 2 Rating

Certification: I certify that the above results were the result of testing on the construction listed above in accordance with the testing procedures and equipment specified by NFPA 260/UFAC Fabric Classification Test Method 1990

Authorized Signature